



SYSTEM COMPONENTS:

LOW FREQUENCY DRIVER:	150-4C
Cone Kit:	C16R1504C
Nom. Impedance:	16 Ohm
Dynamic Test Input V:	14
Sweep Frequency Hz:	20-1200
D.C. Resistance Ohms:	8.8 min/9.3 max
Gap Gauge:	.057"
Notes:	
If Not Serviceable, Replace With:	E145-8
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.
Additional Parts Currently Available*:	
Dome:	21042
Trim Gasket:	52347
HIGH FREQUENCY DRIVER:	375
Diaphragm Kit:	D16R2440
Nom. Impedance:	16 Ohm

HIGH FREQUENCY DRIVER (Cont'd)

Dynamic Test Input V:	3.5
Sweep Frequency Hz:	350-1200
D.C. Resistance Ohms:	7.3 min/8.6 max
Gap Gauge:	.036"
Notes:	537 Horn/509 Lens no longer available. D16R2441 Diaphragm can be used as an alternative. Replace both diaphragms in a stereo pair.
If Not Serviceable, Replace With:	2441
Visual Change:	Yes
Baffle Modification:	No
Exact Acoustic Replacement:	No. Slightly different.
	Replace both units in a stereo pair.

SYSTEM SPECIFICATIONS:

Nom. Impedance:	16 Ohm
Crossover Frequency:	500 Hz
Enclosure Dim:	45-3/4" x 47" x 24-1/2" D 1162mm x 1194mm x 662mm
Shipping Weight:	199 lbs. - 90.2 kg. (empty)

*Other parts may also be available. Check with JBL for details.